

Zip HydroTap



ZIP BRINGS YOU THE MOST INTELLIGENT FILTERED DRINKING WATER TAP EVER INVENTED.

- **Water temperature:** adjustable boiling temperature set point, factory set to operate at 98°C for optimum results. Chilled water 5°C to 14°C.
- **Power-Pulse™** electronic technology controls the set boiling temperature within 0.2°C and eliminates overboil.
- **Choice of fingertip control** for fast cup filling (lever down) or handsfree pot filling (lever up).
- **Can be set** to require finger-thumb safety operation for boiling water access, eliminating the risk of accidental use. Can also be set to boiling isolation mode for increased safety.
- **Longer spout** caters for under-mount sinks. Extended lever & Braille pads also available.
- **Energy saving** technology
- **Low-energy lights** signal boiling water is ready, chilled is ready, or filter change is due.
- **Hidden light sensor** sends appliance to sleep, to conserve energy when the room goes dark.
- **Sleeps or powers off** after 2 hours of non-use.
- **Plus 24/7 on/off timer**, allowing power to be turned off, automatically, for weekday or weekend periods.

NEW G4 ZIP COMMAND-CENTRE™ LEADS THE WORLD IN TIME-SAVING, ENERGY-SAVING TECHNOLOGY.

- **Advanced insulation** and electronics technology reduces standby energy consumption by **up to 55%** over earlier Zip models of similar capacity.
- **Auto-calibrates** to boiling point upon installation, regularly re-calibrates and optimises performance.
- **Simple** pin-code-protected touch-screen puts managers in total control of each appliance.
- **Adjustments include** temperature, dispensing time, safety settings, energy-saving settings.
- **Continuous auto-diagnostics** system monitors performance, provides total history on demand.
- **Integral cross-ventilation** system eliminates cupboard heat-up; no need for an external fan.
- **Multiple filter** life settings, with precise litre monitoring, to optimise filter replacement timing.
- **Added peace-of-mind** features include overload protection, temperature monitoring, internal leak detection, plus an internal pressure limiting valve.

ZIP HYDROTAP NOW SUPPORTS YOUR SUSTAINABILITY AIMS AS NEVER BEFORE.

- **Conserves water.** New, improved air-cooled system with integral cross-ventilation, does not dump water to waste. An environmentally responsible solution.
- **Conserves energy.** Choice of four energy-saving settings to allow site managers to adjust each installation to operate with optimum energy efficiency
- **RoHS Compliant.** All materials involved in Zip HydroTap manufacture comply with the European Restriction of Hazardous Substances Directive 2011/6
- **Red List Compliant.** Designed to meet the sustainable initiatives of the Living Building Challenge by eliminating prohibited materials shown on the LBC Red List.

Five Year Warranty.

Zip HydroTap G4 models shown here are covered by a comprehensive full parts and labour warranty for 24 months from date of purchase. A further 36 months boiling tank warranty is included, provided any service required is carried out by a Zip-trained service provider and that water filter cartridge replacements are made at recommended intervals. Zip HydroTap G3 models are covered by a 12 month warranty. Details are supplied with each appliance and can be viewed at www.zipheaters.co.uk



CUT STANDBY OPERATING POWER USAGE BY UP TO 55%

Zip HydroTap



TECHNICAL DATA

Boiling Filtered Instantly				
Zip Model	Boiling cups/hr		Rating kW @230V	Dimensions W x D x H (mm)
B160G4	160		1.85	280 x 313 x 335
B240G4	240		1.85 + 2.2*	280 x 313 x 335
Chilled Filtered Instantly				
Zip Model	Chilled glasses/hr		Rating kW @230V	Dimensions W x D x H (mm)
C125G4	125		0.2	336 x 476 x 335
C175G4	175		0.25	336 x 476 x 335
Boiling Ambient Filtered Instantly				
Zip Model	Boiling cups/hr		Rating kW @230V	Dimensions W x D x H (mm)
BA160G4	160		1.85	280 x 313 x 335
BA240G4	240		1.85 + 2.2*	280 x 313 x 335
Boiling Chilled Filtered Instantly				
Zip Model	Boiling cups/hr	Chilled glasses/hr	Rating kW @230 V	Dimensions W x D x H (mm)
BC160/175G4	160	175	2.1	450 x 470 x 335
BC240/175G4	240	175	2.1 + 2.2*	450 x 470 x 335
Boiling Chilled Sparkling Filtered Instantly				
Zip Model	Boiling cups/hr	Chilled glasses/hr	Rating kW @230 V	Dimensions W x D x H (mm)
BSC100-75G4	100	75	2.15	280 x 470 x 335
BSC160/175G4	160	175	2.1	450 x 470 x 335

* All Zip HydroTap G4 models rated at 240 cups of boiling water per hour are installed with a 2.2 kW externally mounted booster unit and must be connected to two separate 13 amp power points.



Zip HydroTap Options

FONT AND DRAIN*

Zip HydroTap can be ordered with a matching font and drain for mounting remotely from the sink.

Order Codes:

ZT008 – Standard Chrome **ZT009** – Satin Chrome
ZT010 – Gloss Black **ZT012** – Matt Black

*Not for use with All-in-One. Drainless Font

For locations where there is no available drainage, the Zip “Drainless Font” system ensures the safe and effective collection of waste water from a HydroTap font.

Order Code: **ZT006**



OVER SIZED LEVERS

All HydroTap models, except for models in the All-in-One, Industrial and Miniboil ranges, can be fitted with oversized levers to assist those with restricted dexterity.

Order Codes: Add ‘D’ to normal order code



BRAILLE COVERS

To aid those with sight issues Braille covers can be fitted to these levers.

Order Codes:

SP99910 – Boiling/chilled **SP99911** – Boiling only
SP99912 – Chilled only



SPARKLING CONSUMABLES

Order Codes:

ZT400 – CO2 canister (single).

ZT401 – CO2 regulator

