

# CA MD E



- Centrifugal in-line metal fan
- Backward curved impellers
- 3 speed
- Mounting brackets included
- IP44 Rated

The CA wall external D centrifugal duct fans, for outdoor applications. These fans are manufactured with a steel housing and painted with a polyester paint for long life in all weather conditions. These fans are ideal for ducted installations, have IP44/IPX4 protection, and are designed for domestic and commercial applications.

## Technical Details

Code	Model	Watts	Amps	l/s	Pa	m <sup>3</sup> /hr
		min-max	min-max	min-max	min-max	min-max
16150	CA 100 MD	26-85	0.22-0.40	45-93	195-381	162-334.8
16163	CA 150 MD E	26-85	0.22-0.38	63-148	121-435	226.8-532.8
16165	CA 200 MD E	39-89	0.35-0.43	114-215	353-441	410.4-774
16166	CA 250 MD E	50-120	0.47-0.53	150-280	330-537	540-1008
16167	CA 315 MD E	50-120	0.47-0.53	158-281	353-544	568.8-1011.6

# CA MD E Roof

- Centrifugal in-line metal fan
- Backward curved impellers
- 3 speed
- IP44 Rated

## Technical Details

Code	Model	Watts	Amps	l/s	Pa	m <sup>3</sup> /hr
		min-max	min-max	min-max	min-max	min-max
16140	CA 100 MD E RF	12-50	0.13-0.23	26-73	272-389	93.6-262.8
16183	CA 150 MD E RF	33-85	0.33-0.39	63-136	307-432	226.8-489.6
16185	CA 200 MD E RF	33-95	0.33-0.42	86-194	313-440	309.6-698.4
16186	CA 250 MD E RF	48-130	0.47-0.57	106-236	384-552	381.6-849.6
16187	CA 315 MD E RF	48-130	0.48-0.57	102-240	368-573	367.2-864

## Product Code Terminology

P	Pullcord	M	Metal
T	Timer	E	ERP Compliant
A	Auto Shutter	Q	Quiet
LL	LongLife	D	Dual Speed
PIR	Passive Infrared	TP	Timer Programable
HCS	Humidity Control System	ES	Energy Saving
I	Inbuilt (Recessed)	V0	Self-Extinguishing Plastic
R	Reversible	12V	12V Low Voltage Fan