



# CA V0 E



- Centrifugal in-line self extinguishing V0 plastic fan
- Backward curved impellers
- 3 speed
- Mounting brackets included
- IP44/IPX4 Rated

## Technical Details

| Code  | Model       | Watts   | Amps      | l/s     | Pa      | m3/hr       |
|-------|-------------|---------|-----------|---------|---------|-------------|
|       |             | min-max | min-max   | min-max | min-max | min-max     |
| 16008 | CA 100 V0 D | 14-50   | 0.14-0.22 | 24-69   | 269-366 | 86.4-248.4  |
| 16028 | CA 150 V0 D | 14-52   | 0.14-0.22 | 41-128  | 83-312  | 147.6-460.8 |
| 16038 | CA 200 V0 E | 39-90   | 0.35-0.40 | 107-215 | 241-414 | 385.2-774   |
| 16039 | CA 250 V0 E | 45-90   | 0.37-0.40 | 145-237 | 218-373 | 522-853.2   |
| 16041 | CA 315 V0 E | 48-120  | 0.48-0.54 | 146-305 | 270-554 | 525.6-1098  |

## CA Range Product Accessories

| Code  | Model                                | For Model         |
|-------|--------------------------------------|-------------------|
| 12891 | Trio D Controller                    | For all models    |
| 12971 | SCNRB Built In Controller            | All Models        |
| 22481 | Flush Mounting Kit SCB for C1.5/C2.5 | for C1.5 and C2.5 |
| 22750 | CA-G 100 Protection Grille           | 100 models        |
| 22760 | CA-G 150 Protection Grille           | 150 models        |
| 22765 | CA-G 200 Protection Grille           | 200 models        |
| 22770 | CA-G 250 Protection Grille           | 250 models        |
| 22775 | CA-G 315 Protection Grille           | 315 models        |
| 22551 | Backdraught Shutter 100Ø             | 100 models        |
| 22562 | Backdraught Shutter 150Ø             | 150 models        |
| 22566 | Backdraught Shutter 200Ø             | 200 models        |
| 22571 | Backdraught Shutter 250Ø             | 250 models        |
| 22576 | Backdraught Shutter 315Ø             | 315 models        |

# CA WE D External

- Centrifugal external wall fan
- Backward curved impellers
- 2 speed
- IPX5 Rated

## Technical Details

| Code  | Model         | Watts   | Amps      | l/s     | Pa      | m3/hr       |
|-------|---------------|---------|-----------|---------|---------|-------------|
|       |               | min-max | min-max   | min-max | min-max | min-max     |
| 16091 | CA 100 WE D   | 12-50   | 0.13-0.23 | 18-70   | 180-379 | 64.8-252    |
| 16087 | CA 150 WE D E | 38-100  | 0.36-0.44 | 59-173  | 267-446 | 212.4-622.8 |
| 16089 | CA 200 WE D E | 38-100  | 0.36-0.44 | 60-188  | 244-434 | 216-676.8   |