



### Easi Vent PVC P Flexible Ducting Specifications:

A light wire-reinforced white PVC ducting for domestic applications including cooker hoods and bathroom fans. Standard pitch is 35mm, standard lengths and diameters are listed below.

Code	Description	Box Quantity
P0596/082/26	82mm White PVC Ducting 15m	20
P0092/102/35	102mm White PVC Ducting 3m	72
P0180/102/35	102mm White PVC Ducting 6m	36
P1310/102/35	102mm White PVC Ducting 45m	1
P0092/133/35	133mm White PVC Ducting 3m	48
P0180/133/35	133mm White PVC Ducting 6m	24
P0440/133/35	133mm White PVC Ducting 15m	8
P0180/152/35	152mm White PVC Ducting 6m	18

### Flexible Aluminium Ducting Specifications:

Wire reinforced aluminium ducting with polyester coating for strength. Manufactured to BS476 Parts 6 & 7, Class 0.

Code	Description	Box Quantity
A10M / 102	102mm Aluminium Ducting 10m	1
A10M / 152	152mm Aluminium Ducting 10m	1
A10M / 203	203mm Aluminium Ducting 10m	1

### Flexible Insulated Aluminium Ducting Specifications:

Aluminium ducting with 25mm glass wool insulation to minimise condensation when the ducting travels through a cold area such as a roof space. Manufactured to BS476 Parts 6 & 7, Class 0.

Code	Description	Box Quantity
INSUL / 102 / 10	102mm Insulated Alum Ducting 10m	1
INSUL / 127 / 10	127mm Insulated Alum Ducting 10m	1
INSUL / 152 / 10	152mm Insulated Alum Ducting 10m	1